

Stainless-steel holdback

Stainless-steel holdback



Arrêt de volet Inox matériaux pleins

Description

- A4 stainless steel.
- Stainless-steel holdback for use in solid materials :
 - Bar Ø 10 mm.
 - Use a wall plug Ø 14.
- Stainless-steel holdback for use in breeze blocks or hollow bricks :
 - Supplied with wall plug Ø 12 x 130, fully expanding.
 - Bar Ø 10 mm.
 - Drill hole Ø 12 mm.

Materials



Concrete



Solid breeze block /
Stone



Solid
brick



Breeze block



Hollow Brick

Product benefits

- Made in France.
- Flat screwing section (number 8 spanner) for easy installation.
- Stainless-steel holdback for use in breeze blocks or hollow bricks: Very good hold: the wall plug is anchored across several holes in the substrate.
- Option to fit a stop block before or after installing the holdback.



Arrêt de volet Inox matériaux creux

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	LENGTH	COLOR
ARRET DE VOLET INOX A4 LG 130 Bte de 25	A070320	Boîte de 25	130 mm	Inox A2
ARRET DE VOLET INOX A4 LG 160 Bte de 25	A070330	Boîte de 25	160 mm	Inox A2
ARRET DE VOLET 0/5 PARPAING INOX Bte de 25	A070340	Boîte de 25	190 mm	Inox A2