

Upper shutter stopper, insulation, for espagnolette locking device

For external thermal insulation



Battement haut ISO pour espagnolette

Description

- Upper shutter stopper for espagnolette locking device for external thermal insulation.
- Cataphoresis finish.
- Wall plugs and screws supplied.
- Install before mounting the insulation.
- Height options:
 - 70 mm for non-insulated reveals.
 - 100 mm for insulated reveals.

Materials



Concrete



Solid breeze block / Stone



Solid brick



Breeze block Hollow Brick

Product benefits

- Made in France.

Homologations



CSTB



Battement haut ISO pour espagnolette



Battement haut ISO pour espagnolette - avant isolation



Battement haut ISO pour espagnolette - avant isolation



Battement haut ISO pour espagnolette - après isolation

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	SURCONDT	HEIGHT
BATTEMENT HAUT ISO PIECE D Sachet de 4	A130580	Sachet de 4	5 sachets	70 mm
BATTEMENT HAUT ISO PIECE E Sachet de 4	A130590	Sachet de 4	5 sachets	70 mm
* BATTEMENT HAUT ISO PIECE E L'unité x	A130591	Unité	Aucun	70 mm
BATTEMENT HAUT ISO PIECE R Sachet de 4	A130592	Sachet de 4	5 sachets	70 mm
* BATTEMENT HAUT ISO PIECE S Sachet de 4 x	A130594	Sachet de 4	5 sachets	70 mm
* BATTEMENT HAUT ISO PIECE F Sachet de 4 x	A130600	Sachet de 4	5 sachets	100 mm
BATTEMENT HAUT ISO PIECE J Sachet de 4	A130620	Sachet de 4	5 sachets	100 mm
* BATTEMENT HAUT ISO PIECE G Sachet de 4 x	A130630	Sachet de 4	5 sachets	100 mm

Technical informations - Implementation data

HEIGHT		INSULATION MIN. - MAX.
Part D	70 mm (non-insulated reveals)	100 - 130 mm
Part E	70 mm (non-insulated reveals)	130 - 180 mm
Part R	70 mm (non-insulated reveals)	130 - 200 mm
Part S	70 mm (non-insulated reveals)	190 - 260 mm
Part F	100 mm (insulated reveals)	100 - 130 mm

	HEIGHT	INSULATION MIN. - MAX.
Part J	100 mm (insulated reveals)	130 - 180 mm
Part G	100 mm (insulated reveals)	130 - 200 mm