

Perforated angle bracket

Perforated angle bracket



Équerre perforée

Description

- Galvanised steel S250GD+Z275 in accordance with NF EN 10346.

Product benefits

- Suitable for a variety of timber structures.

Uses

SUBSTRATES:

- Supporting element: wood.
- Supported member: solid wood, composite wood, glued laminated timber, concrete, hollow masonry.

APPLICATIONS:

- Rails, cladding supports, rafters, reinforcing connections etc.

Homologations




ETA 13/0900

Materials



Wood



Équerre perforée - en situation

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDIT	HEIGHT	LENGTH	WIDTH	THICKNESS	FINITION
EQUERRE PERFOREE 60 X 60 X 40 X 2,5 Bte de 100	A471760	Boîte de 100	60 mm	60 mm	40 mm	2,5 mm	Acier
EQUERRE PERFOREE 60 X 60 X 60 X 2 INOX A4 Bte de 50	A471778	Boîte de 50	60 mm	60 mm	60 mm	2 mm	Inox A4
EQUERRE PERFOREE 60 X 60 X 60 X 2,5 Bte de 50	A471780	Boîte de 50	60 mm	60 mm	60 mm	2,5 mm	Acier
EQUERRE PERFOREE 60 X 60 X 80 X 2,5 Bte de 50	A471785	Boîte de 50	60 mm	60 mm	80 mm	2,5 mm	Acier
EQUERRE PERFOREE 80 X 80 X 60 X 2,5 Bte de 50	A471800	Boîte de 50	80 mm	80 mm	60 mm	2,5 mm	Acier

DÉSIGNATION	RÉFÉRENCE	CONDT	HEIGHT	LENGTH	WIDTH	THICKNESS	FINITION
EQUERRE PERFOREE 80 X 80 X 80 X 2,5 Bte de 25	A471820	Boîte de 25	80 mm	80 mm	80 mm	2,5 mm	Acier
EQUERRE PERFOREE 100 X100 X100 X 2 Bte de 20	A471830	Boîte de 20	100 mm	100 mm	100 mm	2 mm	Acier