

2-sided carpentry bracket

2-sided carpentry bracket



Équerre menuiserie 2 pans

Description

- Galvanised steel S250GD+Z275 according to NF EN 10346.
- Thickness 2 mm.

Product benefits

- The oblong holes make it easier to adjust the assemblies.
- They may also be suitable for greater versatility in their use.

Uses

SUPPORTS :

- Supporting element: wood, concrete, steel.
- Supporting element: PVC, wood and aluminium frames.

USES :

- The 2-sided joinery brackets are used to fix PVC, wood and aluminium frames...

Materials



Concrete



Solid breeze block /
Stone



Solid
brick



Aerated concrete



Breeze block



Hollow Brick



Wood

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	HEIGHT	LENGTH	WIDTH	THICKNESS
EQUERRE MENUISERIE 2 PANS 50 X 65 X 30 X 2 Bte de 100	A471603	Boîte de 100	50 mm	65 mm	30 mm	2 mm
EQUERRE MENUISERIE 2 PANS 80 X 65 X 30 X 2 Bte de 100	A471605	Boîte de 100	80 mm	65 mm	30 mm	2 mm
EQUERRE MENUISERIE 2 PANS 100 X 65 X 30 X 2 Bte de 100	A471607	Boîte de 100	100 mm	65 mm	30 mm	2 mm
EQUERRE MENUISERIE 2 PANS 130 X 65 X 30 X 2 Bte de 100	A471610	Boîte de 100	130 mm	65 mm	30 mm	2 mm