

2 thread ISO screw

Double-threaded screw + plug for external insulation

Description

- Fastening of various parts for external insulation.
- Plug Ø 16 + double thread screw Ø12 - M12 or Plug Ø 18 + double thread screw Ø14 - M14.
- Contents: 1 plug, 1 double-threaded screw, 1 threaded washer, 1 washer and 1 nut.

Product benefits

- The threaded washer prevents crushing of the insulation.
- Hexagonal recess on the double-threaded screw to facilitate installation.
- Easy and fast.
- Robust.
- All materials and ideal for hollow materials.
- French made.
- In hollow materials, expansions on several cells of the support.
- 100% polyamide 6 nylon plug.
- Anti-rotation fins.

Materials



Concrete



Solid breeze block / Stone



Solid brick



Breeze block Hollow Brick



Vis 2 filets ISO

Uses

- Fixing parabolas, pergolas, air conditioning supports, ... as part of external insulation.

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDIT	SURCONDIT	DIAMETER	LENGTH	THREAD
VIS 2 FILETS M12 16 X 200 Sachet de 1	A130530	Sachet de 1	5 sachets	16 mm	200 mm	M12
VIS 2 FILETS M12 16 X 240 Sachet de 1	A130540	Sachet de 1	5 sachets	16 mm	240 mm	M12
VIS 2 FILETS M12 16 X 300 Sachet de 1	A130541	Sachet de 1	5 sachets	16 mm	300 mm	M12
VIS 2 FILETS M12 18 X 350 Sachet de 1	A130543	Sachet de 1	5 sachets	18 mm	350 mm	M14

Technical informations - Implementation data

Ø PLUG	PLUG LENGTH	DRILLING		INSULATION MINI-MAXI	
		HOLLOW MATERIALS	SOLID MATERIALS	HOLLOW MATERIALS	SOLID MATERIALS
Ø16 + SCREW Ø12	200 mm	Ø16	Ø17	40-70 mm	90-120 mm
	240 mm	Ø16	Ø17	80-110 mm	130-160 mm
	300 mm	Ø16	Ø17	120-170 mm	170-220 mm
Ø18 + SCREW Ø14	200 mm	Ø16	Ø17	280-220mm	230-270 mm
	240 mm	Ø16	Ø17	230-270 mm	280-320 mm

