

Metal insulation plug Ø35

Hammer-in plug for fixing insulation



Clou isolation métal Ø35

Description

- Hammer-in plug for fixing insulation.
- Ideal for fixing fibralith.
- Ø35 mm head.
- Drilling Ø8 mm.

Product benefits

- Quick and easy: installation through the insulation.
- Fire resistant.
- No drilling in aerated concrete.

Homologations



Materials



Concrete


Solid breeze block /
Stone

Solid
brick


Breeze block



Hollow Brick



Aerated concrete

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDIT	SURCONDIT	HEAD	DRILLING	LENGTH	INSULATION
CLOU ISO METAL 8 / 75 /110 Bte de 250	A270433	Carton de 250	Aucun	Ø 35 mm	Ø 8 mm	110 mm	55 à 75 mm
CLOU ISO METAL 8 / 100 /140 Bte de 250	A270434	Carton de 250	Aucun	Ø 35 mm	Ø 8 mm	140 mm	80 à 100 mm
CLOU ISO METAL 8 / 125 /170 Bte de 250	A270435	Carton de 250	Aucun	Ø 35 mm	Ø 8 mm	170 mm	105 à 125 mm
CLOU ISO METAL 8 / 150 /200 Bte de 250	A270436	Carton de 250	Aucun	Ø 35 mm	Ø 8 mm	200 mm	130 à 150 mm
CLOU ISO METAL 8 / 200 /250 Bte de 200	A270437	Carton de 200	Aucun	Ø 35 mm	Ø 8 mm	250 mm	180 à 200 mm
RONDELLE ISO METAL 80 MM Bte de 250	A270439	Boîte de 250	Aucun	Ø 80 mm	-	-	-