

Wall plug for use in polystyrene

Direct mounting in polystyrene insulation



Cheville polystyrène Ø23 x 50

Description

- Wall plug for lightweight fixings directly in polystyrene insulation.
- No drilling required.
- Average load: 5 kg.

Product benefits

- Quick and easy: Can be screwed directly into insulation.
- 100% polypropylene.

Uses

- Wall-mounted lights, letterboxes, power switches etc. in external thermal insulation.



Cheville polystyrène Ø25 x 57



Cheville polystyrène Ø34 x 60



Cheville polystyrène Ø34 x 90



Cheville polystyrène - vue en situation

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	SURCONDT	DIAMETER	LENGTH
CHEVILLE POUR POLYSTYRENE 23X50 Bte de 25	A136010	Boîte de 25	Aucun	23 mm	50 mm
CHEVILLE POUR POLYSTYRENE 25X57 Bte de 25	A136020	Boîte de 25	Aucun	25 mm	57 mm
CHEVILLE POUR POLYSTYRENE 34X60 Bte de 25	A136023	Boîte de 25	Aucun	34 mm	60 mm
CHEVILLE POUR POLYSTYRENE 34X90 Bte de 25	A136025	Boîte de 25	Aucun	34 mm	90 mm
CHEVILLE POUR POLYSTYRENE 23X50 + VIS Bte de 25	A136055	Boîte de 25	Aucun	23 mm	50 mm
CHEVILLE POUR POLYSTYRENE 23X50 + P.A.VIS Bte de 25	A136065	Boîte de 25	Aucun	23 mm	50 mm
CHEVILLE POLYSTYRENE 23X50 Sachet de 2	A853850	Sachet de 2	5 sachets	23 mm	50 mm
CHEVILLE POLYSTYRENE 25X57 Sachet de 2	A853855	Sachet de 2	5 sachets	25 mm	57 mm
CHEVILLE POLYSTYRENE 34X90 Sachet de 2	A853860	Sachet de 2	5 sachets	34 mm	90 mm
CHEVILLE POLYSTYRENE 34X60 Sachet de 10	A853875	Sachet de 10	5 sachets	34 mm	60 mm
CHEVILLE POLYSTYRENE 34X90 Sachet de 10	A853880	Sachet de 10	5 sachets	34 mm	90 mm

Technical Informations - Dimensions

POLYSTYRENE WALL PLUG	DRIVE FOR SCREWING PLUG	SCREW DIAMETER
Ø 23 X 50	PH n°3	Ø 3 - 4 mm
Ø 25 X 57	Torx T40	Ø 4 - 5 mm
Ø 34 X 60	TH 10	Ø 5 - 6 mm
Ø 34 X 90	TH 13	Ø 6 - 7 mm

Technical informations - Utilisation

