

Countersunk-head hammer-in wall plug

Hammer-in plug with countersunk collar

Description

- Hammer-in plug with countersunk collar.
- The wall plug expands when hammered or screwed in.
- 100% nylon wall plug.
- Grade 5.8 steel screw.

Product benefits

- Quick and easy: expands when hammered through the part to be affixed.
- Grade 5.8 steel screw: not damaged by hammering.
- Collar with large diameter: better plating.
- Countersunk collar.
- Supplied pre-mounted.

Materials



Concrete



Solid breeze block /
Stone



Solid
brick



Cheville Tap-Vis tête fraisée

Uses

- Metal/timber structures, rails for plasterboard, trunking, brackets etc.

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	SURCONDT	DIAMETER	LENGTH
CHEVILLE TAP-VIS TF 5 / 2 / 25 Bte de 100	A270750	Boîte de 100	Aucun	5 mm	25 mm
CHEVILLE TAP-VIS TF 5 / 15 / 45 Bte de 100	A270760	Boîte de 100	Aucun	5 mm	45 mm
CHEVILLE TAP-VIS TF 6 / 5 / 35 Bte de 100	A270765	Boîte de 100	Aucun	6 mm	35 mm
CHEVILLE TAP-VIS TF 6 / 10 / 40 Bte de 100	A270768	Boîte de 100	Aucun	6 mm	40 mm
CHEVILLE TAP-VIS TF 6 / 15 / 45 Bte de 100	A270770	Boîte de 100	Aucun	6 mm	45 mm
CHEVILLE TAP-VIS TF 6 / 25 / 60 Bte de 100	A270772	Boîte de 100	Aucun	6 mm	60 mm
CHEVILLE TAP-VIS TF 6 / 40 / 70 Bte de 100	A270775	Boîte de 100	Aucun	6 mm	70 mm
CHEVILLE TAP-VIS TF 6 / 50 / 80 Bte de 50	A270778	Boîte de 50	Aucun	6 mm	80 mm
CHEVILLE TAP-VIS TF 8 / 5 / 45 Bte de 50	A270780	Boîte de 50	Aucun	8 mm	45 mm
CHEVILLE TAP-VIS TF 8 / 10 / 60 Bte de 50	A270782	Boîte de 50	Aucun	8 mm	60 mm
CHEVILLE TAP-VIS TF 8 / 30 / 80 Bte de 50	A270785	Boîte de 50	Aucun	8 mm	80 mm
CHEVILLE TAP-VIS TF 8 / 60 / 100 Bte de 50	A270790	Boîte de 50	Aucun	8 mm	100 mm
CHEVILLE TAP-VIS TF 8 / 80 / 120 Bte de 50	A270795	Boîte de 50	Aucun	8 mm	120 mm
CHEVILLE TAP-VIS TF 8 / 90 / 135 Bte de 50	A270798	Boîte de 50	Aucun	8 mm	135 mm

		L PLUG LENGTH	D _{CUT} DRILLING DIAMETER	T _{FIX} THICKNESS MAX.	LOAD MAX.
5 / 2 / 25		25 mm	5 mm	2 mm	15 kg
5 / 15 / 45		45 mm	5 mm	15 mm	15 kg
6 / 5 / 35		35 mm	6 mm	5 mm	25 kg
6 / 10 / 40		40 mm	6 mm	10 mm	25 kg
6 / 15 / 45		45 mm	6 mm	15 mm	25 kg
6 / 25 / 60		60 mm	6 mm	25 mm	25 kg
6 / 40 / 70		70 mm	6 mm	40 mm	25 kg
6 / 50 / 80		80 mm	6 mm	50 mm	25 kg
8 / 5 / 45		45 mm	8 mm	5 mm	40 kg
8 / 10 / 60		60 mm	8 mm	10 mm	40 kg
8 / 30 / 80		80 mm	8 mm	30 mm	40 kg
8 / 60 / 100		100 mm	8 mm	60 mm	40 kg
8 / 80 / 120		120 mm	8 mm	80 mm	40 kg
8 / 90 / 135		135 mm	8 mm	90 mm	40 kg

Technical informations - Utilisation

