

Gold wall plug

Wall plug for plasterboard; no drilling required



Cheville Gold

Description

- Metal wall plug for plasterboard; no drilling required.
- Can also be used in fibre-reinforced plasterboard, fibre cement, honeycomb partition walls and 3-mm to 5-mm-thick compressed wood fibre boards.
- Installation with hammer.
- Passivated galvanised steel wall plug with corrosion protection.



Plasterboard

Materials

Product benefits

- No drilling required: quick and easy.
- Screws can be adapted depending on the application: countersunk head, flat head, mounting screw etc.
- Serrated tip: easy and precise insertion.
- Does not rotate when the screw is tightened.
- Flush head.
- Fire-resistant.
- Easy to remove without any marks.

Uses

- Lightweight applications: electric heating systems, ventilation and air-conditioning units, electrical equipment and accessories, plumbing equipment and accessories, wall lighting, TV, shelves, decorative furnishings etc.



Cheville Gold avec
visserie

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	SURCONDT
CHEVILLE GOLD + VIS T.F 4 X 40 Bte de 100	A200060	Boîte de 100	Aucun
CHEVILLE GOLD + VIS T.C 4.2 X 35 Bte de 100	A200070	Boîte de 100	Aucun
CHEVILLE GOLD + PATTE A VIS M7 Bte de 100	A200080	Boîte de 100	Aucun
CHEV. GOLD + VIS Sachet de 10	A858930	Sachet de 10	20 sachets
CHEV. GOLD + P. A VIS M7 Sachet de 10	A858940	Sachet de 10	20 sachets

Technical informations - Implementation data

	Ø VIS SCREW DIAMETER	TFIX THICKNESS MAX.	LOAD MAX.
GOLD WALL PLUG	4 to 4,2 mm	15 mm	15 kg

Technical informations - Utilisation

