


Wall plug for tap

Fixing for mounting a tap in hollow materials

Description

- Fixing for mounting a tap in hollow materials with or without external insulation.
- Double-threaded screw with yellow zinc plating.
- Nuts and washers supplied.
- Wall plug for tap in uninsulated substrates: wall plugs Ø12 x 130, M8 double-threaded screw, M8/M7 pipe nipple fitting.
- Wall plug for tap in insulated substrates: wall plugs Ø12, M8 double-threaded screw, M8/M7 pipe nipple fitting, washer Ø8 x 50.

Materials



Breeze block Hollow Brick



Product benefits

- Quick and easy.
- Made in France.
- Opens up into several holes in the substrate.
- Wall plug 100% nylon polyamide 6.
- Anti-rotation fins.

Homologations



CSTB

cheville robinet de puisage sans
isolation extérieure



cheville robinet de puisage avec isolation
extérieure



cheville robinet de puisage sans isolation extérieure - vue en
coupe



cheville robinet de puisage avec isolation extérieure - vue en
coupe

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	SURCONDIT	LENGTH
CHEVILLE ROBINET 12 X 130 Sachet de 1	A150350	Sachet de 1	5 sachets	130 mm
CHEVILLE ROBINET 16 X 200 Sachet de 1 ---	A150360	Sachet de 1	5 sachets	200 mm
CHEVILLE ROBINET 16 X 240 Sachet de 1 ---	A150370	Sachet de 1	5 sachets	240 mm
CHEVILLE ROBINET 16 X 300 Sachet de 1	A150380	Sachet de 1	5 sachets	300 mm

Technical informations - Implementation data

Ø PLUG	PLUG LENGTH	DRILLING DEPTH	DRILLING	INSULATION MAX.
Ø12 + SCREW Ø10	130 mm	140 mm	Ø12	Without insulation
Ø16 + SCREW Ø12	200 mm	210 mm	Ø16	70 mm
	240 mm	250 mm	Ø16	110 mm

Ø PLUG	PLUG LENGTH	DRILLING DEPTH	DRILLING	INSULATION MAX.
	300 mm	310 mm	Ø16	170 mm