

FIX-SUSPENT®

Adjustable hanger for use directly in concrete for ceilings



FIX-SUSPENT trou lisse

Description

- Adjustable hanger for use directly in concrete for installing metal frames as part of a suspended ceiling.
- Setting tool supplied.
- Drill hole Ø 5 mm.
- Driver adjustment: high torque/low speed.
- Not to be used with an impact wrench.
- Permissible load: 100 kg (factored load with a safety coefficient of 3).
- Thread length: 30 mm.
- Eyelet diameter: 6,5 mm.
- Can be used in hollow-core slabs with a wall plug Ø 8 mm.



Concrete

Materials

Product benefits

- No wall plug required: quick and economical installation.
- Reduced drilling diameter (Ø5): time savings.
- Registered trademark.
- Made in France.
- Adjustable hanger: the threaded rod can be extended or retracted by 25 mm.
- No need to dismount the rail.

Uses

- FIX-SUSPENT unthreaded hole: plasterboard ceilings.
- FIX-SUSPENT M6: suspended ceilings.



FIX-SUSPENT M6



FIX-SUSPENT trou lisse - vue en situation



FIX-SUSPENT M6 - vue en situation



FIX-SUSPENT trou lisse - mise en oeuvre



FIX-SUSPENT M6 - mise en oeuvre

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	SURCONDT	DRILLING
FIX-SUSPENT TROU LISSE Seau de 100	A270410	Seau de 100	Aucun	Ø 5 mm
FIX-SUSPENT M6 Seau de 100	A270420	Seau de 100	Aucun	Ø 5 mm
FIX-SUSPENT M6 Sachet de 25	A858870	Sachet de 25	10 Sachets	Ø 5 mm